

TAIMES®

TF3220



超大幅面高速UV平板打印机

喷头型号 Printhead	高速模式 High speed mode	标准模式 Standard mode	高画质模式 High-quality mode	墨水颜色 Ink Color
RICOH GEN6-5PL 2/3/4/5/6/7/8Heads	720X600dpi 4pass 55sqm/h	720X900dpi 6pass 36sqm/h	720X1200dpi 8pass 26sqm/h	
RICOH GEN5-7PL 2/3/4/5/6/7/8Heads	720X600dpi 4pass 35sqm/h	720X900dpi 6pass 27sqm/h	720X1200dpi 8pass 18sqm/h	
柯尼卡 KM1024I-13PL/6PL 4/5/6/7/8Heads	720X720dpi 4pass 40sqm/h	720X900dpi 6pass 26sqm/h	720X1440dpi 8pass 20sqm/h	

技术参数 Technical Parameters

打印控制 Print Control	
喷墨技术 Print Technology	工业级压电式喷墨打印头 Industrial piezoelectric inkjet
墨水类型 Ink Types	环保UV墨水 Enviromental protective UV ink
RIP软件 RIP Software	Photoprint;Maintop;Printer Factory;
颜色配置 Colour Configuration	4色/6色/白色/光油可选4Color/6Color/White
操作系统 Operating System	Win7/10 64bits
图像格式 Image Format	TIFF/JPEG/EPS/PDF
喷头高度 Printhead Height	可调高度2-100mm Above Media Adjustable
打印材料 Media Type	木面板、铝板、门板、纸板、PVC膨胀板、顶板、玻璃、陶瓷、丙烯酸、PVC等 Wood panel, Aluminum panel, door plank, paperboard, PVC, expansion sheet 、 ceiling panel, glass, ceramics, acrylic, PVC, etc.
介质规格Media Type	板材Panel:3250mm(width)×2050mm(depth)
打印宽度 Printing Width	板材Panel:3200mm(width)×2000mm(depth)
最大材料重量 Maximum Weight of Material	板材 Panel:≤100kg/m
画面干燥系统 Printing Drying System	
UV固化灯 UV Curing Lamp	LED 水冷系统 LED Water Cooling System
数据接口 Data Interface	Hi-Speed USB 2.0
电源要求 Pwer Supply	
最大功率 Maximum Power	> 35A;7.7KW
接入参数Access Parameter	AC220V(±5%),50HZ/60HZ
运行环境 Working Conditions	
湿度 Humidity	35-80% RH(no condensing)
温度Temperature	25-32℃(77to90°F);or more recommended 无疑霜
规格 Specification	
机器尺寸/重量 Machine Dimension/Weight	L5161×2810×H1430mm Net Weight 1000KGS
包装尺寸/重量 Package Dimension/Weight	L5322×3160×H1620mm Net Weight1050KGS

注：由于电脑配置不同，产品速度会有5%差异，具体配置以实物为准，如有技术调整，恕不另行通知
Remark: The data is subject to change without prior notice,the speed will be varied due to different PC settings